



# Material Safety Data Sheet

Revision Date: 06-Nov-2015

Revision Number: 4

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** SUPER SPEC HP URETHANE ALKYD GLOSS ENAMEL ULTRA  
**Product Code** BASE  
**Alternate Product Code** KP224B  
**Product Class** SOLVENT THINNED PAINT  
**Color** All  
**Recommended use** Paint

**Manufacturer** Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
Phone: 855-724-6802  
www.benjaminmoore.com

**Emergency Telephone Number(s)**  
CANUTEC: 613-996-6666

## 2. COMPOSITION INFORMATION ON COMPONENTS

| Chemical Name                                                    | CAS-No     | Weight % (max) |
|------------------------------------------------------------------|------------|----------------|
| Soybean oil, polymer with pentaerythritol and phthalic anhydride | 66070-60-8 | 15 - 40%       |
| Hydrotreated heavy naphtha, petroleum                            | 64742-48-9 | 10 - 30%       |
| Titanium dioxide                                                 | 13463-67-7 | 10 - 30%       |
| Distillates, petroleum, hydrotreated light                       | 64742-47-8 | 3 - 7%         |
| Sunflower oil                                                    | 8001-21-6  | 1 - 5%         |
| Stoddard solvent                                                 | 8052-41-3  | 1 - 5%         |
| Xylene                                                           | 1330-20-7  | 1 - 5%         |
| Linseed oil modified urethane                                    | -          | 1 - 5%         |
| Ethyl benzene                                                    | 100-41-4   | 0.25 - 0.5%    |
| 1,2,4-Trimethylbenzene                                           | 95-63-6    | 0.1 - 0.25%    |
| Methyl ethyl ketoxime                                            | 96-29-7    | 0.1 - 0.25%    |
| Cobalt bis(2-ethylhexanoate)                                     | 136-52-7   | 0.1 - 0.25%    |

## 3. HAZARDS IDENTIFICATION

### Emergency Overview

### **WARNING**

Vapors may be irritating to eyes, nose, throat, and lungs. May cause skin irritation and/or dermatitis. May cause

allergic skin reaction. Combustible material.

Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded.

**Appearance** liquid

**Odor** solvent

**Potential Health Effects**

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Effects**

**Eyes**

Contact with eyes may cause irritation.

**Skin**

May cause skin irritation. May cause allergic skin reaction.

**Inhalation**

May cause irritation of respiratory tract.

**Ingestion**

Ingestion may cause irritation to mucous membranes.

**Chronic Effects** Avoid repeated exposure.

See Section 11 for additional Toxicological information.

**Aggravated Medical Conditions** None known.

**HMIS** - **Health:** 1\* **Flammability:** 2 **Reactivity:** 0 **PPE:** -

**HMIS Legend**

0 - Minimal Hazard

1 - Slight Hazard

2 - Moderate Hazard

3 - Serious Hazard

4 - Severe Hazard

\* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

## 4. FIRST AID MEASURES

**General Advice** If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

**Eye Contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

**Skin Contact** Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.  
If not breathing, give artificial respiration. Call a physician immediately.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.

|                            |                                    |
|----------------------------|------------------------------------|
| Notes To Physician         | Treat symptomatically.             |
| Protection Of First-Aiders | Use personal protective equipment. |

## 5. FIRE-FIGHTING MEASURES

|                                                       |                                                                                                                                                                                                                                            |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable Extinguishing Media                          | Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.                                                                                                         |
| Protective Equipment And Precautions For Firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.                                                                                                     |
| Specific Hazards Arising From The Chemical            | Combustible material. Closed containers may rupture if exposed to fire or extreme heat. Keep product and empty container away from heat and sources of ignition. Thermal decomposition can lead to release of irritating gases and vapors. |
| Sensitivity To Mechanical Impact                      | No                                                                                                                                                                                                                                         |
| Sensitivity To Static Discharge                       | Yes                                                                                                                                                                                                                                        |
| Flash Point Data                                      |                                                                                                                                                                                                                                            |
| Flash Point (°F)                                      | 113                                                                                                                                                                                                                                        |
| Flash Point (°C)                                      | 45                                                                                                                                                                                                                                         |
| Flash Point Method                                    | PMCC                                                                                                                                                                                                                                       |
| Flammability Limits In Air                            |                                                                                                                                                                                                                                            |
| Upper Explosion Limit                                 | Not available                                                                                                                                                                                                                              |
| Lower Explosion Limit                                 | Not available                                                                                                                                                                                                                              |

**NFPA**    Health: 1    Flammability: 2    Instability: 0    Special: Not Applicable

### NFPA Legend

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

*The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.*

*Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).*

## 6. ACCIDENTAL RELEASE MEASURES

|                           |                                                                                                                                                                                                                                                                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal Precautions      | Use personal protective equipment. Remove all sources of ignition.                                                                                                                                                                                                                                |
| Environmental Precautions | Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained. |

|                             |                                                                                                                                            |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Methods For Clean-Up</b> | Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. |
| <b>Other Information</b>    | None known                                                                                                                                 |

## 7. HANDLING AND STORAGE

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Handling</b> | Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.                                                                                        |
| <b>Storage</b>  | Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.<br><br><b>DANGER</b> - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. |

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Limits

| Component                                                              | ACGIH                           | Alberta                                                                                           | British Columbia                                                                         | Ontario                                                                                                       | Quebec                                                                                                        |
|------------------------------------------------------------------------|---------------------------------|---------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| Titanium dioxide<br>13463-67-7 ( 10 - 30% )                            | 10 mg/m <sup>3</sup> - TWA      | 10 mg/m <sup>3</sup> - TWA                                                                        | 10 mg/m <sup>3</sup> - TWA<br>3 mg/m <sup>3</sup> - TWA                                  | 10 mg/m <sup>3</sup> - TWA                                                                                    | 10 mg/m <sup>3</sup> -<br>TWA EV                                                                              |
| Distillates, petroleum,<br>hydrotreated light<br>64742-47-8 ( 3 - 7% ) | N/E                             | N/E                                                                                               | 200 mg/m <sup>3</sup> - TWA<br>Skin absorption<br>can contribute to<br>overall exposure. | N/E                                                                                                           | N/E                                                                                                           |
| Stoddard solvent<br>8052-41-3 ( 1 - 5% )                               | 100 ppm - TWA                   | 100 ppm - TWA<br>572 mg/m <sup>3</sup> - TWA                                                      | 290 mg/m <sup>3</sup> - TWA<br>580 mg/m <sup>3</sup> -<br>STEL                           | 525 mg/m <sup>3</sup> -<br>TWA EV                                                                             | 100 ppm -<br>TWA EV<br>525 mg/m <sup>3</sup> -<br>TWA EV                                                      |
| Xylene<br>1330-20-7 ( 1 - 5% )                                         | 100 ppm - TWA<br>150 ppm - STEL | 100 ppm - TWA<br>434 mg/m <sup>3</sup> - TWA<br>150 ppm - STEL<br>651 mg/m <sup>3</sup> -<br>STEL | 100 ppm - TWA<br>150 ppm - STEL                                                          | 100 ppm -<br>TWA EV<br>435 mg/m <sup>3</sup> -<br>TWA EV<br>150 ppm - STEV<br>650 mg/m <sup>3</sup> -<br>STEV | 100 ppm -<br>TWA EV<br>434 mg/m <sup>3</sup> -<br>TWA EV<br>150 ppm - STEV<br>651 mg/m <sup>3</sup> -<br>STEV |
| Ethyl benzene<br>100-41-4 ( 0.25 - 0.5% )                              | 20 ppm - TWA                    | 100 ppm - TWA<br>434 mg/m <sup>3</sup> - TWA<br>125 ppm - STEL<br>543 mg/m <sup>3</sup> -<br>STEL | 20 ppm - TWA                                                                             | 20 ppm - TWA                                                                                                  | 100 ppm -<br>TWA EV<br>434 mg/m <sup>3</sup> -<br>TWA EV<br>125 ppm - STEV<br>543 mg/m <sup>3</sup> -<br>STEV |

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists  
Alberta - Alberta Occupational Exposure Limits  
British Columbia - British Columbia Occupational Exposure Limits  
Ontario - Ontario Occupational Exposure Limits  
Quebec - Quebec Occupational Exposure Limits  
N/E - Not established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment**

**Eye/Face Protection**

Safety glasses with side-shields.

**Skin Protection**

Long sleeved clothing. Protective gloves.

**Respiratory Protection**

In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

**Hygiene Measures** Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using do not eat, drink or smoke.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                   |               |
|-----------------------------------|---------------|
| <b>Appearance</b>                 | liquid        |
| <b>Odor</b>                       | solvent       |
| <b>Density (lbs/gal)</b>          | 7.8 - 8.2     |
| <b>Specific Gravity</b>           | 0.93 - 0.99   |
| <b>pH</b>                         | Not available |
| <b>Viscosity (centistokes)</b>    | Not available |
| <b>Evaporation Rate</b>           | Not available |
| <b>Vapor Pressure</b>             | Not available |
| <b>Vapor Density</b>              | Not available |
| <b>Wt. % Solids</b>               | 55 - 65       |
| <b>Vol. % Solids</b>              | 45 - 55       |
| <b>Wt. % Volatiles</b>            | 35 - 45       |
| <b>Vol. % Volatiles</b>           | 45 - 55       |
| <b>VOC Regulatory Limit (g/L)</b> | < 400         |
| <b>Boiling Point (°F)</b>         | 279           |
| <b>Boiling Point (°C)</b>         | 137           |
| <b>Freezing Point (°F)</b>        | Not available |
| <b>Freezing Point (°C)</b>        | Not available |
| <b>Flash Point (°F)</b>           | 113           |
| <b>Flash Point (°C)</b>           | 45            |
| <b>Flash Point Method</b>         | PMCC          |
| <b>Upper Explosion Limit</b>      | Not available |
| <b>Lower Explosion Limit</b>      | Not available |

## 10. STABILITY AND REACTIVITY

**Chemical Stability** Stable under normal conditions. Hazardous polymerisation does not occur.

**Conditions To Avoid** Keep away from open flames, hot surfaces, static

|                                           |                                                                           |
|-------------------------------------------|---------------------------------------------------------------------------|
|                                           | electricity and sources of ignition.                                      |
| <b>Incompatible Materials</b>             | Incompatible with strong acids and bases and strong oxidizing agents.     |
| <b>Hazardous Decomposition Products</b>   | Thermal decomposition can lead to release of irritating gases and vapors. |
| <b>Possibility Of Hazardous Reactions</b> | None under normal conditions of use.                                      |

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

#### **Product Information**

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

#### **Component**

##### Hydrotreated heavy naphtha, petroleum

LD50 Oral: > 5,000 mg/kg (Rat) vendor data

LD50 Dermal: > 3,160 mg/kg (Rabbit)

##### Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)

LD50 Dermal: > 10000 mg/m<sup>3</sup> (Rabbit)

LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

##### Distillates, petroleum, hydrotreated light

LD50 Oral: > 5,000 mg/kg (Rat)

LD50 Dermal: > 3,000 mg/kg (Rabbit)

##### Stoddard solvent

LD50 Oral: > 5,000 mg/kg (Rat)

LD50 Dermal: > 3160 mg/kg (Rabbit)

LC50 Inhalation (Vapor): > 6.1 mg/L (Rat)

##### Xylene

LD50 Oral: 4300 mg/kg (Rat)

LD50 Dermal: > 1700 mg/kg (Rabbit)

LC50 Inhalation (Vapor): 5000 ppm (Rat, 4 hr.)

##### Ethyl benzene

LD50 Oral: 3500 mg/kg (Rat)

LD50 Dermal: > 5000 mg/kg (Rabbit)

LC50 Inhalation (Vapor): 55000 mg/m<sup>3</sup> (Rat, 2 hr.)

##### 1,2,4-Trimethylbenzene

LD50 Oral: 5000 mg/kg (Rat)

LC50 Inhalation (Vapor): 18000 mg/m<sup>3</sup> (Rat, 4 hr.)

##### Methyl ethyl ketoxime

LD50 Oral: 930 mg/kg (Rat)

LD50 Dermal: 200 µL/kg (Rabbit)

LC50 Inhalation (Vapor): > 4.8 mg/L (Rat)

### Chronic Toxicity

#### **Carcinogenicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical Name                | ACGIH                                                             | IARC                           | NTP | OSHA Carcinogen |
|------------------------------|-------------------------------------------------------------------|--------------------------------|-----|-----------------|
| Titanium dioxide             |                                                                   | 2B - Possible Human Carcinogen |     | Listed          |
| Ethyl benzene                | A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans | 2B - Possible Human Carcinogen |     | Listed          |
| Cobalt bis(2-ethylhexanoate) |                                                                   | 2B - Possible Human Carcinogen |     |                 |

- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."
- Cobalt and cobalt compounds are listed as possible human carcinogens by IARC (2B). However, there is inadequate evidence of the carcinogenicity of cobalt and cobalt compounds in humans.

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity Effects

### Product Information

#### Acute Toxicity to Fish

No information available

#### Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

### Component

#### Acute Toxicity to Fish

##### Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

##### Xylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

##### Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

Methyl ethyl ketoxime

LC50: 48 mg/L (Bluegill sunfish - 96 hr.)

#### **Acute Toxicity to Aquatic Invertebrates**

Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Methyl ethyl ketoxime

EC50: 750 mg/L (Daphnia magna - 48 hr.)

#### **Acute Toxicity to Aquatic Plants**

Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method** Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

**Empty Container Warning** Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

### 14. TRANSPORT INFORMATION

#### **TDG**

|                             |                       |
|-----------------------------|-----------------------|
| <b>Proper Shipping Name</b> | Paint                 |
| <b>Hazard Class</b>         | 3                     |
| <b>UN-No</b>                | UN1263                |
| <b>Packing Group</b>        | III                   |
| <b>Description</b>          | PAINT,3,UN1263,PG III |

In Canada, Class 3 flammable liquids may be reclassified as non-regulated for domestic ground transportation if they meet the requirements of TDG General Exemption SOR/2008-34.

**ICAO / IATA** Contact the preparer for further information.

**IMDG / IMO** Contact the preparer for further information.

### 15. REGULATORY INFORMATION

#### **International Inventories**

**TSCA: United States** Yes - All components are listed or exempt.

**DSL: Canada** Yes - All components are listed or exempt.

#### **National Pollutant Release Inventory (NPRI)**

##### **NPRI Parts 1- 4**

This product contains the following Parts 1-4 NPRI chemicals:



| <u>Chemical Name</u>         | <u>CAS-No</u> | <u>Weight % (max)</u> | <u>NPRI Parts 1- 4</u> |
|------------------------------|---------------|-----------------------|------------------------|
| Xylene                       | 1330-20-7     | 1 - 5%                | Listed                 |
| Ethyl benzene                | 100-41-4      | 0.25 - 0.5%           | Listed                 |
| 1,2,4-Trimethylbenzene       | 95-63-6       | 0.1 - 0.25%           | Listed                 |
| Cobalt bis(2-ethylhexanoate) | 136-52-7      | 0.1 - 0.25%           | Listed                 |

#### **NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

| <u>Chemical Name</u>                          | <u>CAS-No</u> | <u>Weight % (max)</u> | <u>NPRI Part 5</u> |
|-----------------------------------------------|---------------|-----------------------|--------------------|
| Hydrotreated heavy naphtha,<br>petroleum      | 64742-48-9    | 10 - 30%              | Listed             |
| Distillates, petroleum, hydrotreated<br>light | 64742-47-8    | 3 - 7%                | Listed             |
| Stoddard solvent                              | 8052-41-3     | 1 - 5%                | Listed             |
| Xylene                                        | 1330-20-7     | 1 - 5%                | Listed             |
| 1,2,4-Trimethylbenzene                        | 95-63-6       | 0.1 - 0.25%           | Listed             |

#### **WHMIS Regulatory Status**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

#### **WHMIS Hazard Class**

B3 Combustible liquid

B6 Reactive flammable material

D2A Very toxic materials



## 16. OTHER INFORMATION

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ [http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\\_questions-questions\\_posees-eng.php](http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php).

**Prepared By** Product Stewardship Department  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
855-724-6802

**Revision Date:** 06-Nov-2015  
**Revision Summary** No information available

Disclaimer

---

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

KP224B

**End of MSDS**