



# SUPER KOTE 5000®

## ACRYLIC LATEX ENAMEL LOW-SHEEN EGGSHELL 1130 LINE

### Features

- Premium commercial acrylic latex designed for the professional painter
- No spatter and fast-dry formula provide fast production
- Suitable for use in USDA inspected facilities
- Professional finish withstands washing
- Low odor
- Soap and water clean up
- Low VOC

### General Description

Super Kote 5000® Latex Low-Sheen Eggshell Enamel is designed to be applied with equal success by contractors or do-it-yourselfers. It applies easily without spattering, covers most surfaces in one coat and may be washed repeatedly without film damage. Perfect for bedrooms, hallways or wherever a low-sheen eggshell finish is desirable.

### Recommended For

Interior drywall, plaster, wood, metal, masonry and stucco in commercial, institutional and residential applications. It may be washed repeatedly without film damage. Perfect for bedrooms, hallways or wherever a low-sheen eggshell enamel is desired.

### Limitations

- May be applied when surface and air temperatures are between 50 °F and 90 °F

### Product Information

#### Colors — Standard:

White, Dover White

#### — Tint Bases:

1130-32, Pastel Base  
1130-33, Tint Base  
1130-34, Deep Base  
1130-36, Accent Base

#### — Special Colors:

Contact your dealer.

#### Certification:

The products supported by this data sheet contain a maximum of 100 grams per liter VOC / VOS (0.83 lbs/gal.) excluding water and exempt solvents

This product is currently approved for use under MPI # 44

This product is compliant under the Ozone Transport Commission regulations as a Non-Flat Coating.

This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating.

#### Technical Assistance:

Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-225-5554 or visit [www.coronadopaint.com](http://www.coronadopaint.com).

#### Technical Data◇

#### White

Vehicle Type	Vinyl Acrylic
Pigment Type	Titanium Dioxide
Volume Solids	31.9 ± 1.0%

Coverage per Gallon at Recommended Film Thickness	300 – 400 Sq. Ft.
---	-------------------

Recommended Film Thickness	– Wet	4.0 to 5.3 mils
	– Dry	1.3 to 1.7 mils

Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.

Dry Time @ 77°F (25°C) @ 50% RH	– Tack Free	30 Minutes
	– To Recoat	4 Hours

High humidity and cool temperatures will result in longer dry, recoat and service times.

Dries By	Coalescence
----------	-------------

Viscosity	95 – 100 KU
-----------	-------------

Flash Point	N/A
-------------	-----

Gloss / Sheen	Eggshell 10 – 15 units@85°
---------------	----------------------------

Surface Temperature at Application	– Min.	50°F
	– Max.	90°F

Thin With	Clean Water
-----------	-------------

Clean Up Thinner	Warm, Soapy Water
------------------	-------------------

Weight Per Gallon	11.0 lbs
-------------------	----------

Storage Temperature	– Min.	45 °F
	– Max.	90 °F

#### Volatile Organic Compounds (VOC)

98 Grams/Liter	0.82 Lbs./Gallon
----------------	------------------

◇ Reported values are for White, Contact dealer for values of other bases or colors.

## Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or flaking paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Knife off any protrusions and prime plaster before and after applying patching compound. Remove any powder or loose particles.

**Primers:** New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## Application

Stir thoroughly. Apply by brush (synthetic filament), roller or spray. Length of roller nap depends upon the texture of the surface. Thinning is not usually required for brush or roller application. Apply a full, even coat. Do not apply directly over chalky surfaces or bleeding stains. Apply only when surface and air temperatures are above 50 °F (10 °C).

**Spray, Airless: Fluid Pressure—1,500 to 2,000 PSI;**  
Tip—.017 - .019 Orifice

## Clean Up

Clean up with warm, soapy water followed by a clean water rinse.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

## Environmental Health & Safety Information

**Use only with adequate ventilation.** Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

**WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

**FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL –** Absorb with inert material and dispose of as specified under "Clean up".

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for  
additional health and safety information.**