



SUPER KOTE® 3000

INTERIOR LATEX PRIMER SEALER

948 LINE

Features

- Interior Latex Primer-Sealer
- Excellent Sealing
- Fast Drying
- Water Clean Up

General Description

A high hiding, fast drying Vinyl Acrylic Primer-Sealer for interior dry wall and cured plaster. It is easy to apply and quick drying. It provides an excellent foundation for latex or oil finish coat systems.

Recommended For

For priming and sealing interior walls of plaster, drywall and masonry in commercial, institutional and residential properties. Use under latex or alkyd finishes.

Limitations

- Apply only when surface temperature is above 50 °F (10 °C).

Product Information

<p>Colors — Standard: White</p> <p>— Tint Bases: N/A</p> <p>— Special Colors: Contact your dealer.</p> <p>Certifications & Qualifications: VOC compliant in all regulated areas</p> <p>The products supported by this data sheet contain a maximum of 100 grams per liter VOC/VOS (0.83 lbs. /gal.) excluding water & exempt solvents.</p> <p>This product meets qualifications for LEED (Leadership in Energy and Environmental Design) projects.</p> <p>Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-866-708-9180, or visit www.coronadopaint.com</p>	<table border="1"> <thead> <tr> <th colspan="2">Technical Data◇</th> <th>White</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td></td> <td>Vinyl Acrylic</td> </tr> <tr> <td>Pigment Type</td> <td></td> <td>Titanium Dioxide</td> </tr> <tr> <td>Volume Solids</td> <td></td> <td>32.0 ± 1.0%</td> </tr> <tr> <td>Coverage per Gallon at Recommended Film Thickness</td> <td></td> <td>Up to 450 Sq. Ft.</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet</td> <td>3.6 to 4.6 mils</td> </tr> <tr> <td></td> <td>– Dry</td> <td>1.1 to 1.5 mils</td> </tr> <tr> <td colspan="3">Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.</td> </tr> <tr> <td>Dry Time @ 77 °F (25 °C) @ 50% RH</td> <td>– Tack Free</td> <td>30 Minutes</td> </tr> <tr> <td></td> <td>– To Recoat</td> <td>4 Hours</td> </tr> <tr> <td colspan="3">High humidity and cool temperatures will result in longer dry, recoat and service times.</td> </tr> <tr> <td>Dries By</td> <td></td> <td>Evaporation</td> </tr> <tr> <td>Viscosity</td> <td></td> <td>95 – 102 KU</td> </tr> <tr> <td>Flash Point</td> <td></td> <td>N/A</td> </tr> <tr> <td>Gloss / Sheen</td> <td></td> <td>Flat</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min.</td> <td>50 °F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>90 °F</td> </tr> <tr> <td>Thin With</td> <td></td> <td>Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td></td> <td>Warm Soapy Water</td> </tr> <tr> <td>Weight Per Gallon</td> <td></td> <td>11.8 lbs.</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min.</td> <td>40 °F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>95 °F</td> </tr> <tr> <td colspan="3" style="text-align: center;">Volatile Organic Compounds (VOC)</td> </tr> <tr> <td></td> <td>47 Grams/Liter</td> <td>0.39 Lbs./Gallon</td> </tr> </tbody> </table>	Technical Data◇		White	Vehicle Type		Vinyl Acrylic	Pigment Type		Titanium Dioxide	Volume Solids		32.0 ± 1.0%	Coverage per Gallon at Recommended Film Thickness		Up to 450 Sq. Ft.	Recommended Film Thickness	– Wet	3.6 to 4.6 mils		– Dry	1.1 to 1.5 mils	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.			Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free	30 Minutes		– To Recoat	4 Hours	High humidity and cool temperatures will result in longer dry, recoat and service times.			Dries By		Evaporation	Viscosity		95 – 102 KU	Flash Point		N/A	Gloss / Sheen		Flat	Surface Temperature at Application	– Min.	50 °F		– Max.	90 °F	Thin With		Clean Water	Clean Up Thinner		Warm Soapy Water	Weight Per Gallon		11.8 lbs.	Storage Temperature	– Min.	40 °F		– Max.	95 °F	Volatile Organic Compounds (VOC)				47 Grams/Liter	0.39 Lbs./Gallon
Technical Data◇		White																																																																							
Vehicle Type		Vinyl Acrylic																																																																							
Pigment Type		Titanium Dioxide																																																																							
Volume Solids		32.0 ± 1.0%																																																																							
Coverage per Gallon at Recommended Film Thickness		Up to 450 Sq. Ft.																																																																							
Recommended Film Thickness	– Wet	3.6 to 4.6 mils																																																																							
	– Dry	1.1 to 1.5 mils																																																																							
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.																																																																									
Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free	30 Minutes																																																																							
	– To Recoat	4 Hours																																																																							
High humidity and cool temperatures will result in longer dry, recoat and service times.																																																																									
Dries By		Evaporation																																																																							
Viscosity		95 – 102 KU																																																																							
Flash Point		N/A																																																																							
Gloss / Sheen		Flat																																																																							
Surface Temperature at Application	– Min.	50 °F																																																																							
	– Max.	90 °F																																																																							
Thin With		Clean Water																																																																							
Clean Up Thinner		Warm Soapy Water																																																																							
Weight Per Gallon		11.8 lbs.																																																																							
Storage Temperature	– Min.	40 °F																																																																							
	– Max.	95 °F																																																																							
Volatile Organic Compounds (VOC)																																																																									
	47 Grams/Liter	0.39 Lbs./Gallon																																																																							

◇ Reported values are for White. Contact dealer for values of other bases or colors.

Super Kote® 3000 Interior Latex Primer Sealer 948 Line

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles.

Difficult Substrates: Super Kote® 3000 primer 948-11 works well on many substrates as a primer/sealer. For difficult substrates where a specialty primer might be needed, Insl-x® offers a variety of specialty primers for use over difficult substrates such as bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your dealer can recommend the right Insl-x® problem-solving primer for your special needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer/Finish Systems

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary.

Wood and engineered wood products:

Primer: 1 or 2 coats of Super Kote® 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Bleeding Type Woods, (Redwood and Cedar):

Primer: 1 or 2 coats Super Kote® 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Drywall:

Primer: 1 or 2 coats of Super Kote® 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Plaster:

Primer: 1 or 2 coats of Super Kote® 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Masonry; Rough or Pitted Masonry:

Primer: 1 or 2 coats of Super Kote® 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Masonry; Smooth Poured or Pre-cast Concrete:

Primer: 1 or 2 coats of Super Kote® 3000 Interior Latex Primer Sealer (948 Line)

Finish: 1 or 2 coats of the appropriate Coronado® finish

Repaint, All Substrates: Prime bare areas with the primer recommended for the substrate above.

Application

Stir product with a circular, lifting motion before beginning to paint. Super Kote® 3000 Interior Latex Primer Sealer may be applied by brush, roller, pad or spray, at a rate of application not to exceed 450 square feet per gallon. Surface texture and porosity will affect actual yield. For best brush results, use a quality synthetic filament brush. For roller application, use a 3/8" nap cover for smooth surfaces, a 1/2" nap cover for semi-rough surfaces and a 3/4" to 1" nap cover for rough surfaces. For spray application this Vinyl Acrylic Primer-Sealer may be thinned with clean water.

Clean Up

Clean up with warm, soapy water.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options**

Environmental Health & Safety Information

Cancer Hazard. Contains Crystalline Silica which can cause cancer when in respirable form (spray mist or sanding dust).

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under “CleanUp”.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**